

Spotting Procedures

BRIDGEPOINT
SYSTEMS

degree of difficulty

1 (easiest – complete removal likely)
5 (extremely difficult to remove- limited expectation of success).



Ink - Ink Jet Printer

Description

Time to replace the ink cartridge. Not all the ink always finds the paper. Usually a deep black spill near the printer, but ink may be any of the primary colors. This process applies to liquid inks. For powdered printer inks, see "Copier Toner."

Tools Required

- Extraction equipment
- **Gum Getter** or spotting spatula
- White cotton towels

Chemicals Required

- Bridgepoint **P.I.G. or OINK**
- Bridgepoint **SolventClean or All Solv**
- Bridgepoint **StainZONE**
- Bridgepoint **Encapuguard Green** anti-wicking formula

Procedures

1. Saturate area surrounding the ink with **StainZone**. This creates a barrier that keeps the ink from spreading when as it dissolves.
2. Apply **P.I.G.** or **OINK** to the affected area. **P.I.G.** and **Oink** are very active and will begin to work quickly. Do not allow dwell time. Begin step 3 immediately. Do not allow excessive amounts of solvents to reach the backing. This could lead to delamination.
3. Dry extract. Do not use water. Use vacuum hose to gently agitate and extract.
4. Repeat steps 2 and 3 as long as progress is being made.
5. Apply **Solvent Clean** or **All Solv**. Again, be careful not to allow excessive amounts of solvents to reach the backing.
6. If discoloration persists, apply **StainZONE**. Use **Gum Getter** to work it into the fibers. Allow several minutes dwell time. Extract with very hot water.
7. Apply **Encapuguard Green** and brush into affected area to eliminate possible wicking.

BRIDGEPOINT
SYSTEMS

Bridgepoint Systems To order, call your local Interlink Supply or Bridgepoint Distributor or visit www.InterlinkSupply.com